

PTFE Coated Chemical Resistant Vacuum Pump



WATCH VIDEO

Features

► Chemical resistance & effective

Applied with PTFE-coated diaphragm and pump head with FKM valves, Rocker 300C pumps are adequate to work in milder chemical gases and be cost-effective at the same time.

► Oil-free & care-free

Rocker 300C pumps are driven by diaphragm that needs no lubricant, making them maintenance-free and oil-mist-free.

► Minimized vibration & quiet

Superior weight distribution and assemblies minimize the vibration and noises and maximize stability.

► Overheat protection

Rocker 300C pumps are equipped with overheat protection device that shuts down when overheated and resumes once cooled down, making the pumps safer and long-lasting.

► International certification

CE certification
IP 30 protection
RoHS certification

► Ono-Year Warranty

Applications

- Solvent purification
- Solid-Phase Extraction (SPE)
- Vacuum filtration

Ordering Information

189300-11(22)

Rocker 300C, PTFE Coated Chemical Resistant Vacuum Pump
AC110V, 60Hz (AC220V, 50Hz)



Rocker 300C

* For aggressive solvents and solutions, please refer to Chemker pumps.

Specification

Model	Rocker 300C	
PERFORMANCE DATA		
Max. vacuum	99 mbar abs.	
Max. flow rate	23 L/min @60Hz	20 L/min @50Hz
Hose barb	ID8	
Noise level	50 dB	
Net weight	4.1 Kg	
Dimension (LxWxH)	29 x 14 x 20 cm	
ELECTRICAL DATA		
Voltage	110V	220V
Frequency	50 / 60Hz	
Max. power	65W (1/8 HP)	60W (1/8 HP)
Max. current	0.7A	0.3A
Safety	Overheat Protection	
OTHER DATA		
Equipped with	Glass moisture trap Vacuum regulator	