Stainless Steel Manifold







Features

Quick-assembly and disassembly Each component can be easily removed for cleaning and autoclaving.

► SS316 stainless steel

All wetted parts of MultiVac 301 / 601 manifold are made of SS316 stainless steel, making it durable and autoclavable.

Quick-Fit hose barb

Detachable hose barb can be connected to either side of the manifold quickly towards the vacuum source.

Innovative vent valve design

Adjustable vent valve eliminates water hammer phenomenon and helps drain residual liquid in pipe.

► Individual control valve

Control feeds of each funnel individually.

► Two-Year Warranty

Applications

- ► Microbiological test
- ► Suspended solid test
- ► Vacuum filtration

Ordering Information

180301-02

MultiVac 301 - MB, 3 Places SS Manifold **180601-02**

MultiVac 601 - MB, 6 Places SS Manifold **180100-01**

SF stainless steel funnel, 100 mL

180100-03

SF stainless steel funnel, 300 mL

180100-05

SF stainless steel funnel, 500 mL





Specification

Model	MultiVac 301 - MB	MultiVac 601 - MB
Number of branch	3	6
Filter diameter	47 mm	47 mm
Funnel capacity	100 mL	100 mL
Hose barb	ID8	ID8
Net weight	3.7 Kg	6.6 Kg
Dimension (LxWxH)	48 x 13 x 14 cm	85 x 13 x 14 cm
Part	Material	Material
Body	SS316	SS316
Control valve	SS316	SS316
Adaptor	SS316	SS316
Membrane support	SS316	SS316
Hose barb / Vent valve	SS316	SS316
Handle / Knob	Aluminum	Aluminum
Funnel	SS316	SS316
O-ring	FKM, Silicone	FKM, Silicone

^{*} Materials in contact with the filtrate are SS316, FKM.

