# **Vacuum Filtration System**







# **Features**

## ► For large number of samples

MultiVac 310 / 610 - MS - A is an economical kit for filtration with large number samples.

#### ► Save time & space

Alligator 200 liquid pump bypasses filtrate directly to waste without connecting to additional waste bottles. Saving time for doing tedious cleaning works and more than 40% of bench space.

### Light and handy

This aluminum-made manifold is autoclavable, light and cost-effective.

#### Magnetic filter holder is included

Magnetic filter holder allows one-handed operation and prevents the membrane from being twisted or torn.

#### ► International certification

CE certification IP 64 protection (Alligator 200) RoHS certification (Alligator 200)

- One-Year Warranty (Alligator 200)
- Two-Year Warranty (MultiVac 310 / 610 - MS)

# **Applications**

- ► Suspended solid test
- ► Microbiological test
- ► Vacuum filtration

# **Ordering Information**

### 180311-01(02)-A 180611-01(02)-A

MultiVac 310 / 610 - MS - A, Vacuum Filtration System, complete set includes:

- \* Alligator 200, Diaphragm Liquid Pump
- \* MultiVac 310 / 610 MS, 3 / 6 Places Aluminum Manifold
- \* MF 3, Magnetic Filter Holder, 300 mL (3 / 6 pcs)
- \* Silicone tube





# **Specification**

| Model                          | MultiVac 310 - MS - A                        | MultiVac 610 - MS - A |
|--------------------------------|--|-----------------------|
| PERFORMANCE DATA               |  |                       |
| Max. vacuum                    | 313 mbar abs.                                |                       |
| Max. liquid flow rate          | 4.5 L/min                                    |                       |
| Noise level                    | 60 dB  |                       |
| Net weight                     | 6.5 Kg                                       | 10.3 Kg               |
| Dimension (LxWxH)              | 75 x 19 x 30 cm                              | 114 x 19 x 30 cm      |
| ELECTRICAL DATA                |  |                       |
| Power input                    | DC24V, 1.8A                                  |                       |
| Max. power                     | 44W  |                       |
| Motor                          | Brushless DC Motor (BLDC)                    |                       |
| Safety                         | Overload Protection                          |                       |
| OTHER DATA                     |  |                       |
| Number of branch               | 3  | 6                     |
| Filter holder                  | MF 3, 300 mL x 3                             | MF 3, 300 mL x 6      |
| Filter diameter                | 47 mm  | 47 mm                 |
| Material contact with filtrate | PES, Aluminum, SS316, FKM, Silicone, PP, PPS |                       |