Oil Free Vacuum Pump



Features

Compact & care-free

Rocker oil-free pumps are compact in size, light in weight and oil-mist-free, making them the best pal in laboratory.

Vacuum regulation

Equipped with vacuum gauge and regulator for vacuum monitoring and adjustment.

Overheat protection

All Rocker oil-free pumps are equipped with overheat protection device that shuts down when overheated and resumes once cooled down, making the pumps safer and long-lasting.

Air inlet protection

Filter cartridge at air inlet filters particles and moisture, which prevents pumps from damage.

International certification

CE certification IP 30 certification RoHS certification

Two-Year Warranty

Applications

- ► Vacuum filtration
- Vacuum drying / oven / defoaming
- Suspended solid test
- Microbiological test
- Air sampling

Ordering Information

167910-11(22)

Rocker 910, Vacuum Pump, AC110V, 60Hz (AC220V, 50Hz)

167911-11(22)

Rocker 911, Vacuum Pump, AC110V, 60Hz (AC220V, 50Hz)





Specification

Model	Rocker 910		Rocker 911	
			Rocker 911	
PERFORMANCE DATA				
Max. vacuum	25 mbar abs.		25 mbar abs.	
Max. flow rate	55 L/min @60Hz	45 L/min @50Hz	65 L/min @60Hz	55 L/min @50Hz
Hose barb	ID8		ID10	
Noise level	68 dB		68 dB	
Net weight	7.3Kg		7.0 Kg	
Dimension (LxWxH)	35 x 13 x 21 cm		35 x 13 x 21 cm	
ELECTRICAL DATA				
Voltage	110V	220V	110V	220V
Frequency	50/60Hz		50 / 60Hz	
Max. power	270W (1/3 HP)	250W (1/3 HP)	270W (1/3 HP)	250W (1/3 HP)
Max. current	2.4A	1.2A	2.4A	1.2A
Safety	Overheat Protection		Overheat Protection	
OTHER DATA				
Equipped with	Vacuum regulator Filter cartridge		Vacuum regulator	

* Overflow protection is not included.

