# **Suction System**





### **Features**

### ▶ All in One, saving 50% space

Lafil 300 suction system integrates vacuum source, waste bottle and suction kit into one single system. Saving 50% bench space.

### Safety features

Multiple safety featured designs protect both the operator and the machine.

- (1) Tripping-proof and spill-proof fence-like bottle platform.
- (2) Overflow protection prevents liquid from entering the pump.

### ► Oil-free & care-free

Lafil systems are built-in with oil-free pumps that need no lubricant, making it maintenance-free and oil-mist-free.

#### Autoclavable

The waste bottle and all fittings are made of autoclavable materials such as PES or POM

### ► International certification

CE certification

► Two-Year Warranty (Lafil 300)

### **Applications**

- ► Cell culture aspiration
- ► Laboratory waste suction

## **Ordering Information**

### 197305-11(22)

Lafil 300 - Plus, Suction System AC110V, 60Hz (AC220V, 50Hz)

### 197303-11(22)

Lafil 300 - BioDolphin, Suction System AC110V, 60Hz (AC220V, 50Hz)

### 197300-11(22)

Lafil 300, Vacuum Pump AC110V, 60Hz (AC220V, 50Hz)





### **Specification**

| Model             | Lafil 300 - Plus   |                | Lafil 300 - BioDolphin  |                |
|-------------------|--|----------------|---|----------------|
| PERFORMANCE DATA  |  |                |   |                |
| Max. vacuum       | 99 mbar abs.   |                |   |                |
| Max. flow rate    | 23 L/min @60Hz   | 20 L/min @50Hz | 23 L/min@60Hz   | 20 L/min @50Hz |
| Aspiration rate   | 18 mL/sec  |                |   |                |
| Waste bottle      | PES vacuum bottle, 1200 mL   |                |   |                |
| Noise level       | 50 dB  |                |   |                |
| Net weight        | 5.9 Kg   |                |   |                |
| Dimension (LxWxH) | 34 x 25 x 30 cm  |                |   |                |
| ELECTRICAL DATA   |  |                |   |                |
| Voltage           | 110V   | 220V           | 110V  | 220V           |
| Frequency         | 50 / 60Hz  |                | 50 / 60Hz   |                |
| Max. power        | 65W  | 60W            | 65W   | 60W            |
| Max. current      | 0.7A   | 0.3A           | 0.7A  | 0.3A           |
| Safety            | Overheat Protection  |                |   |                |
| OTHER DATA        | Plus   |                | BioDolphin  |                |
| Suction Kit       | Handle  1-channel tip adaptor (150 mm)  1-channel tip adaptor with ejector  8-channel tip adaptor with ejector |                | Handle  1-channel tip adaptor (50 mm)  1-channel tip adaptor (150 mm)  1-channel SS adaptor (40 mm)  1-channel SS adaptor (80 mm)  8-channel SS adaptor (40 mm)  1-channel tip adaptor with ejector  8-channel tip adaptor with ejector  Rack |                |