

COD Detector



Features

► **Use reagents of your choice**

CD 200 detector reads reagents from different brand owners. Pre-programmed with Hach, Lovibond and CHEMetrics parameters, or set up by yourself.

► **Wide measure range**

CD 200 can measure COD values in 3 different ranges: 10 ~ 150 mg/L, 100 ~ 1500 mg/L and 1000 ~ 15000 mg/L.

► **Fast detection**

CD 200 can detect and save COD value in 3 seconds.

► **Data storage up to 100 records**

The built-in memory can store up to 100 records for easy access.

► **International certification**

CE certification

► **One-Year Warranty**

CD 200



Applications

- Wastewater analysis from factories
- Water monitoring, such as surface water and groundwater
- Environment monitoring in lake, pond and river

Ordering Information

198200-01 (02)

CD 200, COD Detector with AC100-240V adaptor, US plug (EU plug)

Specification

Model	CD 200
PERFORMANCE DATA	
Display	LCD with backlight
Brands of reagents	HACH, Lovibond, CHEMetrics
Measure range	10 ~ 150 mg/L, 100 ~ 1500 mg/L, 1000 ~ 15000 mg/L
User-defined curve	6 curves
Light source	LED
Working wavelength	420 nm, 610 nm (automatic)
Detecting time	3 sec
Optical stability	≤ 0.005 Abs / 30 min
Storage	100 records
Data information	Concentration, sample number, time
Net weight	0.5 Kg
Dimension (LxWxH)	23 x 13 x 9 cm
ELECTRICAL DATA	
Power input	DC12V, 1.0A
Power supply	DC9V battery or power adaptor
Max. power	1W